

# Swd Rheinol Antifreeze GW 12

## -40°C

## Longlife Antifreeze Readymix for Motor Vehicles

### Description and Application

**Swd Rheinol Antifreeze GW 12 (-40°C)** is a ready water-diluted antifreeze based on ethylenglycole, to be used for all motor vehicles, which require silicate-free products (e.g. Ford, GM and MAN). It is applicable for all established engines inclusive the modern high performance aluminium-motors. It is compatible with all coolant brands( also VW G 11).

### Swd Rheinol Antifreeze GW 12 (-40°C)

- may be used a life time through for grey iron - and alu motors
- protects all metallic materials in the system
- is eco friendly, because it is free of nitrites, amines, phophates and silicates
- provides all-seasons protection of the cooling system

### Specification / Recommendations

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>❖ VW/Audi/Seat/Skoda TL744-D/F (G12/12+)</li> <li>❖ John Deere JDM H5</li> <li>❖ Opel-GM GMW 3420</li> <li>❖ Renault-Nissan 41-01-001/-S Type D</li> <li>❖ Caterpillar A4.05.09.01</li> <li>❖ Cummins IS series u N14</li> <li>❖ Komatsu 07.892 (2009)</li> <li>❖ Deutz/MWM 0199-99-2091/8</li> <li>❖ Volvo 014 GS 17009</li> </ul> | <ul style="list-style-type: none"> <li>❖ MB 325.3</li> <li>❖ MAN 324 SNF</li> <li>❖ MTU MTL 504B</li> <li>❖ Jenbacher TA 1000-0201</li> <li>❖ Fiat MAT3624</li> <li>❖ Mazda MEZ MN 121 D</li> <li>❖ Liebherr MD1-36-130</li> <li>❖ Ford WSS-M97B44-D</li> </ul> |
|--|---|

### Technical Properties

Swd Rheinol Antifreeze GW 12 -40°C	unit	value
Density at 20°C	kg/m <sup>3</sup>	1076
Colour		violett
Pour Point	°C	-40
Flash Point	°C	>100
pH		8,6
Boiling Point	°C	>100

**Article-Number : 39140**

Specification variations in these characteristics may occur.  
The instructions of manufacturer must be regarded.  
Further informations to be available by MSDS.

**Swd Lubricants GmbH & Co. KG**  
Am Schlütershof 26  
D-47059 Duisburg  
Tel.: 0203 / 3191940  
Fax: 0203 / 3466540