



Swd Rheinol Primol Power Synth

SAE 10W-40

High Performance Low Friction Motor Oil for Passenger Cars

Description and Properties

Swd Rheinol Primol Power Synth SAE 10W-40 is a semi-synthetic low friction oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality synthetic components and mineral base stocks and additives of most progressive technology.

Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged.

Swd Rheinol Primol Power Synth SAE 10W-40 by its optimized formulation provides lowered fuel- and oil consumption. Because of its extended viscosity range the all seasons use is possible. The dispersing power, expressed by the performance level of this product, prevents deposits and pluggings in the oil circuit and thus keeps the engine clean. Modern oxidation inhibitors extend the service life of the oil and the optimal wear protection cares for long engine life.

Specifications / Recommendations

ACEA A3 / B4
API SL / CF
VW 505 00
Renault RN 0700
PSA B71 2296

Approvals

MB-approval 229.1

Typical Properties

Swd Rheinol Primol Power Synth SAE 10W-40	unit	value	method
Density at 15°C	kg/m ³	861	DIN 51 757
Viscosity at 40°C	mm ² /s	97,1	DIN 51 562
Viscosity at 100°C	mm ² /s	14,7	DIN 51 562
Viscosity Index		158	DIN ISO 2909
CCS at -25°C	mPa.s	5310	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	10,1	DIN ISO 3771

Article-Number : 31345

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191999