



Swd Rheinol Primus ASM

SAE 5W-30

High Performance Fuel Economy Oil for Passenger Cars

Discription and Properties

Swd Rheinol PRIMUS ASM SAE 5W-30 is a high-alloyed all-season oil for those passenger car engines, which require fuel economy (FE) oils. The low viscosity of specific base oils used in this product, based on Synthesis-Technologie, provides a prompt motor lubrication combined with supremely low frictional resistance, which leads to an appreciable reduction of fuel consumption and pollutant emission. Suitable for use with DPF.

Swd Rheinol PRIMUS ASM SAE 5W-30 matches all thermic- and mechanical loads, which may occur in modern fuel economy passenger car engines.

- high cleaning- and dirt holding capacity (Detergent/Dispersant) provide excellent motor cleanliness.
- outstanding fuel economy properties by special friction reducing additives.
- cost-effective all-season oil with appreciable fuel reduction.
- environmentally sound by reducing emissions of CO₂ and particles.

Specifications / Recommendations

ACEA C2/A1/B1, A5/B5
 API SN
 ILSAC GF-5
 Toyota, Mitsubishi
 Subaru, Honda, Mazda

Hyundai, KIA
 Renault RN 0700
 PSA B71 2290
 Fiat 9.55535-S1

Typical Properties

Swd Rheinol Primus ASM SAE 5W-30	unit	value	method
Density at 15°C	kg/m ³	851	DIN 51 757
Viscosity at 40°C	mm ² /s	64,1	DIN 51 562
Viscosity at 100°C	mm ² /s	11,0	DIN 51 562
Viscosity Index		165	DIN ISO 2909
CCS at -30°C	mPa.s	5390	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	236	DIN ISO 2592
TBN	mg KOH/g	8,5	DIN ISO 3771

Article-No. : 31189

Specification variations in these characteristics may occur.
 The instructions of manufacturer must be regarded.
 Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
 Am Schlütershof 26
 D-47059 Duisburg
 Phone: 0203 / 31919-0
 Fax: 0203 / 3191999