



Swd Rheinol Primus VO

SAE 0W-20

Special high-performance engine oil for Volvo Engines

Description and Properties

Swd Rheinol Primus VO SAE 0W-20 is a special high-performance engine oil based on synthesis technology. It has been developed specifically for use in Volvo engines. This special additive-technology ensures an excellent lubrication safety.

Through the combined effect of low viscosity with the specially developed additives high fuel saving is made possible and thus the reduction of CO₂ - emissions. Modern engines make caused by downsizing and modern start-stop systems more and greater demands on the engine oil. These are guaranteed with superior wear characteristics and additional power reserves by the new technology.

The used additive-package has been specially developed for the high demands of the new Volvo VCC RBS0-2AE.

Specifications / Recommendations

ACEA C5

VOLVO VCC RBS0-2AE

Typical Properties

Swd Rheinol Primus VO SAE 0W-20	unit	value	method
Density at 15°C	kg/m ³	845	DIN 51 757
Viscosity at 40°C	mm ² /s	48	DIN 51 562
Viscosity at 100°C	mm ² /s	9,1	DIN 51 562
Viscosity Index		177	DIN ISO 2909
CCS at -35°C	mPa.s	5980	DIN 51 377
Pourpoint	°C	-48	DIN ISO 3016
Flashpoint	°C	236	DIN ISO 2592

Article-No. : 31188

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Phone: 0203 / 31919-0
Fax: 0203 / 3191999