



Swd Rheinol Primus GF-5 Plus

SAE 5W-20

Fully Synthetic Fuel Efficient Engine Oil

Description and Properties

Swd Rheinol Primus GF5 Plus SAE 5W-20 is a high performance lubricant, which especially is designed for the most advanced gasoline and diesel engines of passenger cars, which are operated with low viscosity fuel saving engine oils. It is suitable for use in all types of modern vehicles where this viscosity grade is recommended. This includes high-performance turbo-charged, supercharged gasoline multi-valve fuel injected engines found in passenger cars and light vans.

Swd Rheinol Primus GF5 Plus SAE 5W-20 is designed on base of synthetic oils only. It persuades by an excellent lubricity and shows outstanding properties and benefits :

- stable lubrication film at all operation conditions
- outstanding cold starting properties even at low temperatures
- long motor life by complex wear protection and cleanliness from cylinder head down to oil sump
- low oil consumption and high fuel efficiency
- lower environmental impact by reduced exhaust gas emissions and long oil drain intervals

Specifications / Recommendations

API SP	Daihatsu	Mazda
ILSAC GF-6A	Honda	Nissan
GM dexos1 Gen 2	Kia	Subaru
Ford WSS-M2C960	Isuzu	Suzuki
Chrysler MS-6395	Lexus	Toyota

Typical Properties

Swd Rheinol Primus GF-5 Plus SAE 5W-20	unit	value	method
Density at 15°C	kg/m ³	852	DIN 51 757
Viscosity at 40°C	mm ² /s	47,5	DIN 51 562
Viscosity at 100°C	mm ² /s	8,5	DIN 51 562
Viscosity Index		157	DIN ISO 2909
CCS at -30°C	mPa.s	4750	ASTM D5293
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	8	DIN ISO 3771

Article-No. : 31169

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlüttershof 26
D-47059 Duisburg
Phone: 0203 / 31919-0
Fax: 0203 / 3191999